



Av. Europa, nº 12
17800 OLOT
(Girona) SPAIN

Tel. (+ 34) 972 265 100
Fax (+ 34) 972 266 366

xucla@xucla.es
www.xucla.es

ISO 9001

BUREAU VERITAS
Certification



Code	Description
CV2500	STEAM COOKER 2500 L.

Tecnic description

Total sizes:

Length 2.800 mm.

Width 1.620 mm.

Height 1.700 mm.

Tank dimensions:

Length 2.478 mm.

Width 982 mm .

Height 1.145 mm.

Construction

Tank, superior part and lid made of stainless steal AISI 316.

The rest made of stainless steal AISI 304.

Capacity: 2.500 liters.

Two compensated tilting lids. From 10° aperture, the lids keep their position automatically.

Tank made of sheet 3 mm.

Antivibrator adjustable feet M20.

Insulation: 90mm of an insulation layer called wool of rock 60 mm .

Valve water feeding 1" inox.

Drain valve 2" inox.

Stainless steal valve to steam feeding 1 ¼" (Maximum pressure 1,5 kg/cm²).

Valve to drain condensed ¾".

Water heating by direct injection of steam.

Colander filter situated at the steam entrance.

Steam consummation: 400 Kg/h.

Returning water system to the tank by means of a stainless steal motor pump.

It drafts the central and superior water and is propelled at the bottom of the tank with a three times superior force.

Stainless steal moto pump 1.1 kW.

Electric remote control switchboard

Handling 24 VAC.

Protected motor pump, running luminous indicators. General switch, push-buttons.

Regulator de temperature electronic - digital , with sensor PT-100.